

HIGH TEMPERATURES PREMIUM SUBMERSIBLE WINDING WIRE



CONDUCTOR	OVERALL DIAMETER (Nominal)	CONDUCTOR CROSS-SECTIONAL AREA (Nominal)	CONDUCTOR RESISTANCE AT 20°C (MAX)	Elongation (Min.) %
Sq. mm.	MM	MM	Ohms/km	
0.70	1.10	0.385	44.78	28
0.80	1.20	0.503	34.30	29
0.90	1.35	0.636	27.10	30
1.00	1.45	0.786	21.95	30
1.10	1.55	0.951	17.50	31
1.20	1.65	1.131	15.26	32
1.30	1.75	1.328	12.58	32
1.40	1.85	1.540	11.20	32
1.50	2.00	1.768	9.75	32
1.60	2.10	2.011	8.57	32
1.70	2.20	2.271	7.59	32
1.80	2.30	2.546	6.77	32
1.90	2.40	2.836	6.08	32
2.00	2.50	3.143	5.49	33
2.10	2.60	3.465	4.98	33
2.20	2.70	3.803	4.53	33
2.30	2.80	4.156	4.15	33
2.40	2.90	4.526	3.81	33

***Note:** Lesser and Higher OD are available as on demand.

**Reliable Quality
With Strong
Performance**